



1550 Medium

- **Water- en stofdicht, en drukbestendig**
- Gemakkelijk te openen tweestapsluitingen
- Open celkern met stevig wandontwerp - sterk, licht
- O-ringafdichting
- Automatisch drukequalisatieventiel - houdt de inwendige druk in evenwicht en het water buiten
- Comfortabele rubberen handgrepen
- Roestvrij stalen structuur en hangslotbeschermers
- 2 Lagen Pick N Pluck® plukschuim
- [Gepersonaliseerd naamplaatje beschikbaar](#)
- [Lifetime Guarantee of Excellence](#)

CONFIGURATIES

- 1550** - Standard
- 1554** - With With Padded Dividers
- 1550NF** - With No Foam
- 1550TP** - With With TrekPak Divider System

AFMETINGEN

- Interior (L x W x D):** 18.63 x 14.18" x 7.72 (47.3 x 36 x 19.6 cm)
- Exterior (L x W x D):** 20.66 x 17.20" x 8.40 (52.5 x 43.7 x 21.3 cm)
- Lid Depth:** 1.75"
- Bottom Depth:** 5.87"
- Total Depth:** 7.62"
- Int Volume:** 1.18 ft³


MATERIAAL

- Body:** Polypropylene
- Latch:** ABS
- O-Ring:** Polymer
- Pins:** Stainless Steel
- Foam:** 1.3 lb Polyurethane
- Purge Body:** ABS
- Purge Vent:** 3 Micron Hydrophobic Non-Woven
- Purge O-Ring:** 70 Shore Nitrile

KLEUREN




Black




Silver



Orange



Yellow



OD Green



Desert Tan

WEIGHT

Weight With Foam: 11.90 lbs

Weight Without Foam: 10.58 lbs

Buoyancy: 69.89 lbs

Master Pack Weight: 28.35 lbs

TEMPERATUUR

Minimum Temperature: -40°

Maximum Temperature: 210°

CERTIFICERINGEN

IP67

MIL C-4150J

Def Stan 81-41

STANAG 4280

ATA 300

FOAM PROPERTIES

Layer 1 (Lid): 1.75" Convolute

Layer 2 (Base): 0.75" Pad

Layer 3 (Base): 2.50" Pick N Pluck

Layer 4 (Base): 2.50" Pick N Pluck

ANDERE

Master Pack: 2

Nameplate: Ja

Military: Ja

Pelican Products, Inc.

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com