

1620

Groot



- Uittrekbaar handvat
- **Stevige wielen uit polyurethaan met roestvrij stalen lagere**
- Gemakkelijk te openen tweestapsluitingen
- Open celkern met stevig wandontwerp - sterk, licht
- O-ringafdichting
- Automatisch drukequalisatieventiel - houdt de inwendige druk in evenwicht en het water buiten
- Inklapbare handvaten
- Roestvrij stalen structuur en hangslotbeschermers
- 4 Lagen Pick N Pluck® plukschuim
- [Gepersonaliseerd naamplaatje beschikbaar](#)
- **Water- en stofdicht, en drukkbestendig**

CONFIGURATIES

- 1620** - Standard
- 1624** - With With Padded Dividers
- 1620NF** - With No Foam

AFMETINGEN

- Interior (L x W x D):** 21.48 x 16.42" x 12.54 (54.6 x 41.7 x 31.9 cm)
- Exterior (L x W x D):** 24.76 x 19.57" x 13.90 (62.9 x 49.7 x 35.3 cm)
- Lid Depth:** 2.01"
- Bottom Depth:** 10.53"
- Total Depth:** 12.54"
- Int Volume:** 2.56 ft³


MATERIAAL

- Body:** Polypropylene
- Latch:** ABS
- O-Ring:** Polymer
- Pins:** Stainless Steel
- Foam:** 1.3 lb Polyurethane
- Purge Body:** ABS
- Purge Vent:** 3 Micron Hydrophobic Non-Woven
- Purge O-Ring:** 70 Shore Nitrile

KLEUREN



Black



OD Green



Desert Tan

WEIGHT

Weight With Foam: 24.62 lbs

Weight Without Foam: 21.20 lbs

Buoyancy: 149.91 lbs

Master Pack Weight: 26.90 lbs

TEMPERATUUR

Minimum Temperature: -40°

Maximum Temperature: 210°

CERTIFICERINGEN

IP67

MIL C-4150J

Def Stan 81-41

STANAG 4280

FOAM PROPERTIES

Layer 1 (Lid): 1.00" Convolute

Layer 2 (Base): 1.00" Pad

Layer 3 (Base): 2.38" Pick N Pluck

Layer 4 (Base): 2.38" Pick N Pluck

Layer 5 (Base): 2.38" Pick N Pluck

Layer 6 (Base): 2.38" Pick N Pluck

ANDERE

Wheels: 2

Extendable Handle: Ja

Master Pack: 1

Nameplate: Ja

Military: Ja

Pelican Products, Inc.

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

sales@pelican.com • www.pelican.com